

Declaration of performance according to Regulation EU 305/2011



No. Varia A-FDh 10,4 kW - 2020-01

1. General	
Unambiguous identification code for the product type	Varia A-FDh 10,4 kW
Intended use	Space heating in buildings with potential heating and process water preparation
Manufacturer	Spartherm Feuerungstechnik GmbH Maschweg 38, D-49324 Melle Deutschland - www.spartherm.com
System(s) to assess and review constancy of performance	3
Notified laboratory	confirms type test according system 3
Notified body/ies	RRF, D-46047 Oberhausen / 1625
Test report No.	RRF 29 12 2948
Harmonised standard	DIN EN 13229 :2001/ A2:2004/ AC:2007
2. Declared performance	
Reaction to fire	A1
Fire safety	passed
Distance to combustible materials	Floor: 0 cm Sides: 8 cm Front: 110 cm
Risk of burning fuel falling out	passed
Emission of combustion products	0.1 %
Surface temperature	passed
Electrical safety	no performance determined / npd
Release of dangerous substances	npd
Cleanability	passed
Max. operating pressure	npd
Flue gas temperature	253 °C
Mechanical strength (for the installation of flue outlet)	npd
Nominal heat output	10,4 kW
Water heating capacity	0
Room heating capacity	10,4 kW
Efficiency	>80 %
The efficiency of the above product corresponds to the declared performance. The above-mentioned manufacturer is solely responsible for drawing up the declaration of performance in accordance with the Regulation (EU) no. 305/2011.	

Signed for and in the name of the manufacturer by:

Gerhard Manfred Rokossa

Nr. Varia A-FDh 10,4 kW - 2020-01

1. Genrelt	
Unik identifikationskode for produkttypen:	Varia A-FDh 10,4 kW
Anvendelse	Rumopvarmning i bygninger med mulighed for varmtvands- og brugsvandsrensning
Producent	Spartherm Feuerungstechnik GmbH Maschweg 38, D-49324 Melle Deutschland - www.spartherm.com
System(er) til bedømmelse og kontrol af ydelsesbestandigheden	3
Afprøvningssted	System 3 afprøvning
Notificeret/notificerede organ(er)	RRF, D-46047 Oberhausen / 1625
Prøvningsrapport Nr.	RRF 29 12 2948
Harmoniseret standard	DIN EN 13229 :2001/ A2:2004/ AC:2007
2. Erklæret/erklærede ydelse®	
Brændforhold	A1
Brandsikkerhed	opfylder
Afstand til brandbare materialer	Gulv: 0 cm Side: 8 cm Foran: 110 cm
Brandfare p.g.a ufald af træ	opfylder
Emission af forbrændingsprodukter	0.1 %
Overfaldetemperatur	opfylder
Elektrisk sikkerhed	der er ikke konstateret nogen ydeevne / npd
Udslip af farlige stoffer	npd
Renlighed	opfylder
Max. driftstryk	npd
Afgastemperatur	253 °C
Mekanisk stabilitet (til installation af røggasaftræk)	npd
Nominelydelse	10,4 kW
Nominel vandydelse	0
Rumvarmeydelse	10,4 kW
Wirkningsgrad	>80 %
<p>Det ovenstående produkts ydelse svarer til den/de erklærede ydeevne(r). Ovennævnte producent bærer det fulde ansvar for udarbejdelsen af ydeevnedeklarationen i overensstemmelse med (EU-) forordning nr. 305/2011.</p>	

Underskrevet for producenten og på vegne af producenten af:

Gerhard Manfred Rokossa

